

UNICO® PowerSpin™ Series tabletop centrifuges are economical, reliable and super quiet. The UNICO® fixed speed PowerSpin™ FX model spins at 3400 RPM, while the variable speed LX spins at 300-4000 RPM, insuring a clean, complete separation of cellular components yielding a superior serum or plasma specimen.

The LX models (C856 and C858) meet CLIA recommendations for accurate speed control; it is simply the most economical model on the market to help your lab pass CLIA inspections.



Features and Specifications:

- Standard 6 or 8 place rotor for 2 to 10 ml tubes
- Adapters required for 2 ml or 3-5 ml tubes (part # C800-04 and C800-0)
- 0-30 minute timer with bell tone signal
- Quiet at full speed, only 58 decibels
- Latching lid with safety switch triggered to shut-off power to the motor when the lid is raised
- Stainless Steel rotor chamber is easily accessible for cleaning and disinfection
- UL approved components
- Maintenance-free brushless motors
- Suction cup rubber feet for stability while reducing vibration
- Lid window for strobe tachometer RPM check

Centrifuge Size:	10.2 x 11.8x 7.9 "
Shipping Size:	13.4x14.8x10.6 "
Net Weight:	15 lbs.
Shipping Weight:	18 lbs.
Warranty:	One year

C800-01	8 Place Rotor with tube shields
C800-02	Regular tube shield, pack of 2
C800-03	Adapters for 3-5 ml tubes, pack of 10
C800-04	Adapters for 2 ml and smaller tubes, pack of 2
C800-10	Fuse 250A 4A, each

UNICO Model	Item Number	Speed	Max. RCF (g)	Angled Rotor
PowerSpin™ FX	C806	3400 RPM	1350	6 place
PowerSpin™ FX	C808	3400 RPM	1350	8 place
PowerSpin™ LX	C856	300 – 4000 RPM	1830	6 place
PowerSpin™ LX	C858	300 – 4000 RPM	1830	8 place

UNITED PRODUCTS & INSTRUMENTS

182 Ridge Road, Suite E Dayton, New Jersey 08810
 Tel: 800-588-9776 * Fax: 732-274-1155
 E-mail: info@unicosci.com * Web: www.unicosci.com